



WEATHERPROOF™ Tar Roof Resaturant #41115

A Select blend of refined coal tar pitch, aromatic solvents, non-asbestos fibers and fillers, and wet adhesion surfactants, that is designed for compatibility and rejuvenation of coal tar pitch roofing systems.

Uses

- A cold applied coating/resaturant for use with coal tar pitch BUR roofing.
- Waterproofing and dampproofing of concrete and masonry surfaces.

Advantages

- Highly resistant to chemical and ultraviolet attack.
- Extends the life of coal tar pitch roofing systems.
- Unique self-healing properties and ponding water resistance make it ideal for no to low slope roofs.
- Meets current VOC requirements.
- Cold applied with a trowel and cures to a tough, durable protective barrier.
- Non Asbestos.
- Federal Specification SS-C-540B (except, non-asbestos).

INSTALLATION

APPLICATION

- Ready to apply. Do not heat. Do not thin.
- In cold weather, store product at 70-80°F for 24 hours prior to application or use an OSHA approved pail/drum heater.

Surface Preparation

- All surfaces must be clean, free of heavy dirt, dust, debris, oils, loose gravel, un-adhered coatings, loose, scaling rust, deteriorated membranes, and other contaminants that may result in a surface that is not sound.
- Surface must be free of frost, snow and ice.

Surface Preparation (continued)

- Aggregate must be spud away to provide a proper work surface.
- Fasteners must be repaired and/or replaced as needed.

Directions:

- Apply to the prepared surface at a rate of 2-4 gallons per square if used as a coating over metal or composition roofs.
- Apply to the prepared gravel surfaced roof at a rate of 4-8 gallons per square.
- Re-embed gravel.

Application Precautions:

- **Do not** use with or on 100% rubber or plastic substrates.
- **Do not** use on or with products containing asphalt.
- **Do not** use where this product may come in contact with potable water..
- **Do not thin.**
- **Exterior use only.**

Clean Up:

- Immediately rinse/flush equipment and tools with an OSHA approved aromatic solvent after use, exercising all flammable liquid precautions.
- Use waterless hand cleaner on skin.

Cautions

- This product is combustible. Keep away from heat, sparks, and open flame. Avoid breathing of vapors. Avoid repeated or prolonged contact with skin. If swallowed, do not induce vomiting. Contact Physician immediately. Keep container closed when not in use. **KEEP AWAY FROM CHILDREN.** Product label and Material Safety Data Sheet contain further information on the safe use of this product and precautions for the safe disposal of the container. They should be read and understood prior to use.

Packaging:

- 5-gallon pails (52 lbs)

Specification Compliances:

- Federal Specification SS-C-540B (except, non-asbestos)

SPECIFICATIONS

PROPERTY	TEST METHOD	RESULT
Wt/gal, lbs.	D6511	8.8-9.2
Solids, %by wt.	D6511	87-92
%by vol.		83-87
Viscosity, grams	Stormer to 200 revolutions	500-1500
pH		N/A
Flash Point, ° F	PMCC	105 min.
Color, uncured & cured	Visual	Black
Drying time, Touch	70 ° F/50% R.H.	8 hours
Shelf Life	70 ° F/50% R.H.	1 year
VOC	EPA Method 24A	200 gm/liter max.