



HAZARDOUS POLYMERIZATION: Will not occur.

## SECTION 6 – HEALTH HAZARD DATA

ROUTES OF EXPOSURE: Inhalation, Ingestion, Skin Contact, Eye Contact.

HEALTH HAZARDS (ACUTE): Possible irritant.

HEALTH HAZARDS (CHRONIC): Possible irritant.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Preexisting eye, skin, respiratory disorders may be aggravated by exposure to this product.

Ingredients are not considered carcinogenic by OSHA, NTP or IARC monographs.

**EMERGENCY AND FIRST AID PROCEDURES:** EYE CONTACT: Flush with clean water for at least 15 minutes. Seek medical attention. SKIN CONTACT: Remove contaminated clothing, wash with soap and water. IF INHALED: Remove person to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, administer artificial respiration. Seek medical attention. IF INGESTED: Do not induce vomiting. Contact Poison Control Center, seek medical attention.

## SECTION 7 – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED: Eliminate sources of ignition. Ventilate area, if necessary. Dike and contain spill with inert material (e.g. clay, sand, earth). Prevent material from entering sewers or waterways. Recover free liquid. Transfer absorbed material into non-leaking, sealable containers for proper disposal.

WASTE DISPOSAL: Dispose of material in accordance with applicable Federal, State and local regulations. This material is a RCRA regulated hazardous waste. EPA hazardous waste number: D001 – Ignitable.

PRECAUTIONS FOR STORAGE AND HANDLING: Keep away from sources of ignition. Use only with adequate ventilation. Avoid prolonged or repeated contact with skin. Follow "Special Protection Information".

## SECTION 8 – CONTROL MEASURES

RESPIRATORY PROTECTION: Normally not required in ventilated areas. If TLV is exceeded a NIOSH/MSHA approved breathing apparatus is recommended.

VENTILATION: If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional ventilation or exhaust systems may be required.

PROTECTIVE GLOVES: Solvent resistant gloves.

EYE PROTECTION: Wear safety glasses, chemical goggles, or face shield.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Long pants and long sleeved shirts are recommended to reduce material contact with skin. Shoes with non-skid soles are also recommended.

WORK/HYGENIC PRACTICES: Always follow good housekeeping practices. Avoid contact with surfaces where material will not be applied.

SECTION 9 – OTHER INFORMATION

ABBREVIATIONS	NA=NOT APPLICABLE	HEALTH	NFPA	HMIS
	ND=NOT DETERMINED	FLAMMABILITY	1	1
	NE=NOT ESTABLISHED	REACTIVITY	2	2
		PERSONAL PROTECTION	0	0

VOC Content: Less than 550 grams/liter. Complies with California, Massachusetts and Federal regulations in effect on date of issuance.

DOT Proper Shipping Name: Combustible Material, NOS, 3, NA 1993, PG III  
Contains Petroleum Distillates

The information contained herein is believed to be accurate and complete to the best of ALCM's knowledge at the time of issuance. ALCM does not warranty the accuracy of this data and shall not be liable for any loss or damage arising from the use thereof.